


PRESS® N/L 10

SBR,



(N), (L),

SBR/EPDM,

UNI EN ISO 1307/97

5 : ± 0,60

8 – 20 : ± 0,80

20 – 25 : ± 1,20

>25 : ± 1,60

: ± 1%

-30 °C +80 °C

Code	5	8	10	12	15	20	25
IH30102102/100	5	2,75	10,5	10	30	0,10	30
IH30101001/100	8	3,5	15	10	30	0,19	50
IH30101002/100	10	2,5	15	10	30	0,15	60
IH30101003/100	10	3,5	17	10	30	0,22	60
IH30101004/100	12	2,5	17	10	30	0,17	70
IH30101005/100	13	3	19	10	30	0,23	80
IH30101006/100	15	3	21	10	30	0,25	90
IH30101007/100	16	3,5	23	10	30	0,32	100
IH30101008/80	19	3,5	26	10	30	0,37	110
IH30101009/80	20	5	30	10	30	0,59	120
IH30101010/80	22	4	30	10	30	0,49	130
IH30101011/50	25	4	33	10	30	0,55	150
IH30101012/50	25	5	35	10	30	0,70	150
IH30101013/40	30	6	42	10	30	1,00	180
IH30101014/40	32	6	44	10	30	1,07	190

RUBBER HOSE PRESS 10 bar MADE IN ITALY Parker ITR