


POLIAX® UPE SM EN 12115
EN 12115, TRbF 131 Part 2 par. 5.5 (огнестойкость)


(UHMWPE),

EPDM,

(R < 1 M /m),

0,9

EN 12115

POLIAX UPE SM EN 12115

19 – 38 : ± 0,50

50 : ± 0,70

>63,5 : ± 0,80

31 – 51 : ± 1,00

66 – 91 : ± 1,20

>91 : ± 1,60

: ± 1%

EN 12115, TRbF 131 / 2 par. 5.5

25 ° (77 °F),

-15 °C +100 °C

+100 °C

IH36811501/40	19	6	31	16	64	0,710	190
IH36811502/40	25	6	37	16	64	0,870	230
IH36811503/40	32	6	44	16	64	1,070	260
IH36811504/40	38	6,5	51	16	64	1,350	340
IH36811505/40	50	8	66	16	64	2,290	410
IH36811507/40	63,5	7,75	79	16	64	2,510	450
IH36811508/40	75	8	91	16	64	3,070	530
IH36811510/20	100	8	116	12	48	4,430	680

EN 12115 UPE - I. D. - SD - PN... - BP... bar - M - TRbF 131/T2 P.5.5 - Quarter/Year - MADE IN ITALY Parker ITR