



aerospace
climate control
electromechanical
filtration
fluid & gas handling
hydraulics
pneumatics
process control
sealing & shielding



Sandblast Couplings



ENGINEERING YOUR SUCCESS.

j – Sandblast Couplings

Working pressure

10 bar (150 psi)

Working temperature

-30 °C (-22 °F) up to +70 °C (+158 °F)

Hose, coupling, assembly method and seal must be chosen in relation with the desired application and temperature range.

Materials

- Malleable iron, zinc plated
- Nylon

Features

- Hose assembly is completed inside the coupling, hose is fixed by screws from outside
- Standard claw distance 58 mm for all sizes
- Couplings of malleable iron are very robust, while nylon couplings are used for weight reasons

Threads

- Female BSP - EN ISO 228-1
- Female coarse thread 50 mm - ANSI B1.1

Sandblast couplings

Material: **Malleable iron, zinc plated or nylon**
 For hose type: **LIBECCIO**
 Claw distance: **58 mm**
 Assembly:

Safety Clamps	Worm Drive	Bolt clamps	Crimping
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>



Part-No.	Hose I.D. x wallthickness	Height	Width	Weight kg/pcs
SBS19	19 x 6 mm	100	63	0,40
SBS25	25 x 7 mm	93	87	0,48
SBS32	32 x 8 mm	92	87	0,57
SBS38	38 x 9 mm	129	87	0,78
SBS40	40 x 10 mm	150	87	0,89



Part-No.	Hose I.D. x wallthickness	Height	Width	Weight kg/pcs
SBS32T	G 1 1/4"	55	87	0,39
SBS38T	G 1 1/2"	55	87	0,34
SBS50T	G 2"	84	87	0,55
SBS50MT	Coarse thread 50 mm	55	87	0,32



Part-No.	Hose I.D. x wallthickness	Thread	Height	Width	Weight kg/pcs
SBNA32	32 x 8 mm	G 1 1/4"	130	57	0,25
SBNA50	32 x 8 mm	Coarse thread 50 mm	130	57	0,23



Part-No.	Hose I.D. x wallthickness	Height	Width	Weight kg/pcs
SBN19	19 x 6 mm	110	51	0,19
SBN25	25 x 7 mm	110	51	0,17
SBN32	32 x 8 mm	136	60	0,22
SBN38	38 x 9 mm	136	67	0,24
SBN40	40 x 10 mm	136	71	0,22



Part-No.	Hose I.D. x wallthickness	Height	Width	Weight kg/pcs
SBN32T	G 1 1/4"	63	61	0,13
SBN50MT	Coarse thread 50 mm	63	61	0,11



Part-No.	Hose I.D. x wallthickness	Thread	Height	Width	Weight kg/pcs
SBNN19M	19 x 7 mm	Coarse thread 50 mm	100	49	0,115
SBNN25M	25 x 7 mm	Coarse thread 50 mm	100	93	0,93
SBNN32M	32 x 8 mm	Coarse thread 50 mm	120	59	0,15
SBNN38M	38 x 9 mm	Coarse thread 50 mm	128	68	0,156
SBNN19	19 x 7 mm	G 1 1/4"	100	51	0,109
SBNN25	25 x 7 mm	G 1 1/4"	100	51	0,102
SBNN32	32 x 8 mm	G 1 1/4"	128	59	0,154
SBNN38	38 x 9 mm	G 1 1/4"	128	66	0,166