



RADIOR DIN 6

EPDM,



DIN 73411-1996

UNI EN ISO 1307/97

38 : ± 0,79

> 38 : ± 1,59

: ± 1,59

: ± 1%

40

1

-40 °C +125 °C

Code	Length (mm)	Inner Diameter (mm)	Outer Diameter (mm)	Thread	Length (mm)	Weight (g)	Traceability
IH30836101/40	10	3,5	17	6	18	0,17	--
IH30836102/40	12	3,5	19	6	18	0,20	--
IH30836103/40	13	3,5	20	6	18	0,21	--
IH30836104/40	15	3,5	22	6	18	0,23	--
IH30836105/40	16	3,5	23	6	18	0,25	--
IH30836106/40	18	3,5	25	6	18	0,27	--
IH30836107/40	20	3,5	27	6	18	0,30	--
IH30836108/40	22	3,5	29	6	18	0,33	--
IH30836109/40	25	4,5	34	6	18	0,48	--
IH36836110/40	28	4	36	6	18	0,52	--
IH36836111/40	30	4	38	6	18	0,55	--
IH36836112/40	32	4	40	6	18	0,58	--
IH36836113/40	35	4	43	6	18	0,63	--
IH36836114/40	38	5	48	6	18	0,88	--
IH36836115/40	40	5	50	6	18	0,92	--
IH36836116/40	42	5	52	6	18	0,96	--
IH36836117/40	45	5	55	6	18	1,02	--
IH36836118/40	48	5	58	6	18	1,07	--
IH36836119/40	50	5	60	6	18	1,11	--
IH36836120/40	51	5	61	6	18	1,13	--
IH36836121/40	55	5	65	6	18	1,21	--
IH36836122/40	60	5	70	6	18	1,28	--
IH36836123/40	64	5	74	6	18	1,42	--
IH36836124/40	65	5,5	76	6	18	1,52	--
IH36836125/40	70	5,5	81	6	18	1,64	--
IH36836126/40	75	5,5	86	6	18	1,74	--
IH36836127/40	76	5,5	87	6	18	1,76	--
IH36836128/40	80	6	92	6	18	2,03	--
IH36836129/40	90	6	102	6	18	2,26	--
IH36836130/40	100	6,5	113	6	18	2,71	--
IH36836131/40	110	6,5	123	6	18	2,98	--