



## VARIOPRESS N/L 10 - 20

EPDM,

(R&lt;1 MΩ/ )

-40 °C +100 °C (

120 °C)



UNI EN ISO 1307/97

5 : ± 0,60

8 - 19 : ± 0,80

25 : ± 1,20

: ± 1%

|--|--|--|--|--|--|--|--|

### VARIOPRESS N/L 10

IH30113007/100	5		11	10	30	0,10	30
IH30113000/100	8	3,5	15	10	30	0,17	50
IH30113008/100	10	3	16	10	30	0,16	60
IH30113010/100	13	3	19	10	30	0,20	80
IH30113030/100	16	3,5	23	10	30	0,29	100
IH30113013/80	19	4	27	10	30	0,39	115
IH30113012/50	25	5	35	10	30	0,63	150

### VARIOPRESS N/L 20

IH30113020/100	10	4,5	19	20	60	0,27	60
IH30113025/100	12	3	18	20	60	0,19	70
IH30113027/40	13	3,5	20	20	60	0,25	80
IH30113027/100	13	3,5	20	20	60	0,25	80
IH30113037/100	16	4,5	25	20	60	0,4	100
IH30113047/80	19	5,5	30	20	60	0,57	115
IH30113042/50	25	6	37	20	60	0,79	150

**RUBBER HOSE VARIOPRESS W.P. bar MADE IN ITALY Parker ITR**